


# QGSD(DNC)

## 系列(ISO15552:2004)标准缸 series ISO15552:2004 standard cylinder



### 图形符号 Graphical symbols



### 产品特点 Features

QGSD (DNC) 系列轻型气缸符合ISO15552国际标准外形采用方形结构, 机械强度及精度高, 外侧带有磁性开关槽, 具有工作可靠, 耐久性好, 互换性强的特点。安装、连接尺寸与DNC相同。

QGSD (DNC) series cylinder, standard ISO1555 2s, square tube, features reliable performance, high durability and interchangeability. All install dimension are same as DNC series.

### 型号注释 Order Code

QGSD D - 50 x 50 - 25 - K - LB Y(A/B)

型号 / Mode
动作形式 / motion pattern 无标记Blank: 标准复动型 / standard double acting D-双轴复动型 / Double-shaft double acting J- 双轴可调行程型 / double-shaft and adjustable stroke type
缸径 / cylinder bore
行程 / stroke
可调行程 / adjustable stroke
磁石代号 / Magnet code K:附磁石 / with magnet 空白: 不附磁石 / Blank: no magnet
固定形式 / Fixed Type: 空白blank-基本型 / basic type LB-前后固定型 / front and back fixed type FA-前盖固定型(前法兰) / front cover fixed type (front flange type) FB-后盖固定型(后法兰) / rear cover fixed type(rear flange type) CA-后盖固定型(单耳环) / rear cover fixed type (single earring) CB-后盖固定型 (双耳环) / rear cover fixed type (double earring)
活塞杆端连接形式 (与SI相同) / Rod end connection(the same as SI) Y(A/B): 杆端Y(A/B)型连接件 /rod end Y(A/B) connector I: 杆端I型连接件 /Rod end type I connector

### 技术参数 Specification

缸径 Bore	32	40	50	63	80	100	125
动作形式 / Motion type	复动型 / Double Acting						
工作介质 / Working medium	干燥洁净含油雾的压缩空气 Dry and cleaned compressed air containy lubricant						
固定型式 / Fixed type	基本型, LB型, FA型, FB型, CA型, CB型 / Basic type, LB type, FA type, FB type, CA type, CB type						
工作压力范围 / Working pressure range (MPa)	0.15~1						
保证耐压力 / ensured pressure resistance (Mpa)	1.5						
工作温度 / Working temp. (°C)	-5~50						
活塞运动速度范围 / Speed of piston (mm/s)	50~800						
缓冲形式 / Cushion type	可调缓冲 / adjustable Cushion						